

OW-8

ECO BOOST GASOLINE ENGINE OIL

Royal Super Fully Synthetic Motor Oil is a fuel-efficient and environmentally friendly universal motor oil, developed according to the most recent technology and based on specially selected synthetic base oils to which advanced additives are added to obtain the below performance levels.

<mark>1L, 2L, 3L, 4L, 5L, 6L</mark> 20L, 25L















60L, 208L, 1000L 25,000L



TDS / MSDS Please visit our website www.royalsuper.ae or send request to info@royalsuper.ae | sales@royalsuper.ae



Description

Royal Super Full Synthetic Engine Oil API SP SAE 0W8 is an advanced fully synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the below features. It makes great fixing between the cylinder and chamber, safeguards the motor at various temperatures and keeps up with ideal consistency for the best motor performance. Royal Super gives great wear control to safeguard the motor in various atmospheric conditions and unforgiving applications, protecting the motor in cold climate fire up and warm climate conditions

Features



Provides excellent overall performance.



Excellent low temperature capabilities for rapid engine protection at start-up



Enhanced frictional properties that aids fuel economy



Delivers fast protection for reduced engine wear and deposits even in the most extreme driving conditions



Provides exceptional cleaning power for dirty engines

Performance Level



TDS / MSDS Please visit our website www.royalsuper.ae or send request to info@royalsuper.ae | sales@royalsuper.ae





Specification

TESTS	METHOD	RESULTS
Appearance	VISUAL	C&B
Water	HOT PLATE	NIL
Color	ASTM 1500	L3
Density @29.5°C,gm/CC	ASTM D 4052	0.842
Viscosity @100°C, cSt	ASTM D 445	5.3
Viscosity @40°C, cSt	ASTM D 445	26.1
Viscosity Index	ASTM D 2270	140
Pour Point, °C	ASTM D 97	-42
Flash Point, □C	ASTM D 92	228
TBN, mgKOH/gm	ASTM D 2896	7.8
Foam Characteristics	ASTM 892	
SEQ I		0/0
SEQ II		0/0
SEQ III		0/0

PACKAGE SIZE

1L,2L,3L,4L,5L,6L-[CAN]20L,25L-[PAIL]60L,200L,208L-[DRUM]1000L,25,000L-[IBC] Customize Packing