

**ECO BOOST
 PETROL ENGINE OIL**

Royal Super Fully Synthetic Motor Oil is a fuel-efficient and environmentally friendly universal motor oil, developed according to the most recent technology and based on specially selected synthetic base oils to which advanced additives are added to obtain the below performance levels.

1L, 2L, 3L, 4L, 5L, 6L / 20L, 25L



60L, 208L, 1000L / 25,000L



Description

Royal Super Full Synthetic Engine Oil API SN/CF SAE 20W60 is an advanced fully synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the below features. It makes great fixing between the cylinder and chamber, safeguards the motor at various temperatures and keeps up with ideal consistency for the best motor performance. Royal Super gives great wear control to safeguard the motor in various atmospheric conditions and unforgiving applications, protecting the motor in cold climate fire up and warm climate conditions

Features

- ✓ Provides excellent overall performance.
- ✓ Excellent low temperature capabilities for rapid engine protection at start-up
- ✓ Enhanced frictional properties that aids fuel economy
- ✓ Delivers fast protection for reduced engine wear and deposits even in the most extreme driving conditions
- ✓ Provides exceptional cleaning power for dirty engines

Performance Level



API SN/CF

Specification

| TESTS | METHOD | RESULTS |
|-----------------------|-------------|---------|
| Appearance | VISUAL | C&B |
| Water | HOT PLATE | NIL |
| Color | ASTM 1500 | L3 |
| Density @29.5°C,gm/CC | ASTM D 4052 | 0.878 |
| Viscosity @100°C, cSt | ASTM D 445 | 25 |
| Viscosity @40°C, cSt | ASTM D 445 | 234 |
| Viscosity Index | ASTM D 2270 | 135 |
| Pour Point, °C | ASTM D 97 | -27 |
| Flash Point, □C | ASTM D 92 | 232 |
| TBN, mgKOH/gm | ASTM D 2896 | 7.8 |
| Foam Characteristics | ASTM 892 | |
| SEQ I | | 0/0 |
| SEQ II | | 0/0 |
| SEQ III | | 0/0 |

PACKAGE SIZE

1 L , 2 L , 3 L , 4 L , 5 L , 6 L - [CAN] 20 L , 25 L - [PAIL] 60 L , 208 L - [DRUM] 1000 L , 25,000 L - [IBC]

Customize Packing