



# ECO BOOST PETROL ENGINE OIL

Royal Super Fully Synthetic Motor Oil is a fuel-efficient and environmentally friendly universal motor oil, developed according to the most recent technology and based on specially selected synthetic base oils to which advanced additives are added to obtain the below performance levels.

### <mark>1L, 2L, 3L, 4L, 5L, 6L</mark> 20L, 25L















## 60L, 208L, 1000L 25,000L



TDS / MSDS Please visit our website www.royalsuper.ae or send request to info@royalsuper.ae | sales@royalsuper.ae





P5W-60

Royal Super Full Synthetic Engine Oil API SN/CF SAE 25W60 is an advanced fully synthetic motor oil designed to keep your engine running like new by providing exceptional wear protection, cleaning power and overall performance. A fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the below features. It makes great fixing between the cylinder and chamber, safeguards the motor at various temperatures and keeps up with ideal consistency for the best motor performance. Royal Super gives great wear control to safeguard the motor in various atmospheric conditions and unforgiving applications, protecting the motor in cold climate fire up and warm climate conditions

#### Features



Provides excellent overall performance.



Excellent low temperature capabilities for rapid engine protection at start-up



Enhanced frictional properties that aids fuel economy



Delivers fast protection for reduced engine wear and deposits even in the most extreme driving conditions



Provides exceptional cleaning power for dirty engines

**Performance Level** 



TDS / MSDS Please visit our website www.royalsuper.ae or send request to info@royalsuper.ae | sales@royalsuper.ae





#### **Specification**

TESTS	METHOD	RESULTS
Appearance	VISUAL	C&B
Water	HOT PLATE	NIL
Color	ASTM 1500	L3
Density @29.5°C,gm/CC	ASTM D 4052	0.878
Viscosity @100°C, cSt	ASTM D 445	25
Viscosity @40°C, cSt	ASTM D 445	234
Viscosity Index	ASTM D 2270	135
Pour Point, °C	ASTM D 97	-27
Flash Point, □C	ASTM D 92	232
TBN, mgKOH/gm	ASTM D 2896	7.8
Foam Characteristics	ASTM 892	
SEQ I		0/0
SEQ II		0/0
SEQ III		0/0

#### PACKAGE SIZE

1L,2L,3L,4L,5L,6L-[CAN]20L,25L-[PAIL]60L,208L-[DRUM]1000L,25,000L-[IBC] Customize Packing

TDS / MSDS Please visit our website www.royalsuper.ae or send request to info@royalsuper.ae | sales@royalsuper.ae